


# Color SA plus

High quality, low-emission interior wall paint with micro-silver as a film preserver for protection against fungal attack

| Colour | Availability | | |
|---|---|---|---|
| | Quantity per pallet | 48 | 32 |
| | **Size / Quantity** | **5 l** | **12,5 l** |
| | Type of container | Plastic bucket | Plastic bucket |
| | Container code | 05 | 13 |
| | **Art. no.** | | |
| white | 2984 | ■ | ■ |

## Application rate




Approx. 0.15 l/m² per coat (depending on the substrate condition).
Apply to a large enough trial area to determine the precise amount required.

## Range of use



- Surfaces at risk of mould, e.g. in living rooms, schools, nurseries, offices, hotels, restaurants, wellness facilities
- Finishing coat on mineral wall formers, renders, gypsum plasterboard, raw fibre and fibreglass wallpaper, adhering old coatings
- In areas for people sensitive to mould (children, people with allergies)

## Property profile




- Water vapour diffusion capable
- Hard-wearing and resistant to scrubbing (wet abrasion class 2 as per DIN EN 13300)
- Good hiding power (class 2 as per DIN EN 13300)
- Gloss level: matt

## Characteristic data of the product

**On delivery**

| | |
|---|---|
| Binder | Pure acrylate binder |
| Density (20 °C) | Approx. 1.15 kg/l |
| Viscosity | Suitable for application |
| pH value (20 °C) | Approx. 8 |

**Once fully cured**

| | |
|---|---|
| Colour | White |
| Degree of gloss | Dull matt |

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

## Additional information

› **Sustainability Data Sheet**

## Possible system products

› **Primer Hydro HF (0725)**

## Preparation

**Substrate requirements**
Dry, clean, free of dust and cracks (except hairline cracks) and capable of supporting a load.
Structural deficiencies such as heat bridges must be eliminated.
Condensation must be avoided.

**Substrate preparation**

Completely remove any superficial mould infestation using Remmers Mould Stop*.

## Directions




**Conditions for use**
Temperature of the material, air and substrate: from min. +8 °C to max. +25 °C.

Stir well.
Coat the surface using a suitable tool.
Apply the material in 2 coats, depending on the condition of the substrate.
Wait at least 8 hours between coats.

## Tips on use

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.
The first coat can be diluted with up to 5% water.

## Notes

Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.
Always set up a trial area/trial areas first.

## Tools / Cleaning



Paintbrush, flat brush, lamb's wool roller, ceiling brush

Clean tools with water while the material is still fresh.
Clean splashed material with water while the material is still fresh.

**Remmers tools**

- **Flächenstreicher (4540)**
- **Farbrolle FC (4913)**
- **Rollerbügel (4449)**
- **Pro nylon roller (5045)**
- **Collomix® stirrer LX (4296)**
- **Patentdisperser (4747)**

## Storage / Shelf life




If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.

## Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

## Disposal

Larger product residues must be disposed of in the original packaging in accordance with the applicable regulations. Do not pour liquid coating or residues down the drain, even when cleaning tools. Must not be disposed of with household waste. Completely empty packaging must be recycled.

## Biocidal Products Regulation

Contains as "treated goods" a biocidal product (film preservative) with the biocidal active agent silver phosphate glass to protect the film from contamination by microbial organisms (algae, mould etc.). Always follow the directions carefully!

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

## VOC content as per the "Decopaint" Directive (2004/42/EC)

EU limit value for the product (Cat. A/a): max. 30 g/l (2010).
This product contains < 30 g/l VOC.




Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never be binding, even though it is provided to the best of our knowledge In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.